






provided by



Levels of Designation

Component/system			
	ROOF	SILVER	GOLD
ROOF <ul style="list-style-type: none"> • Roof deck attached with 8d ring shank nails • Roof deck sealed • Roof cover is high wind rated [or necessary engineering] (if spacing is too tight the engineering note can be omitted) 	✓	✓	✓
ATTIC VENTILATION <ul style="list-style-type: none"> • Roof-mounted vents are high-wind rated • Gable end vents are protected against water intrusion 	✓	✓	✓
OVERHANGS <ul style="list-style-type: none"> • Soffit vents will resist water intrusion 	–	✓	✓
OPENINGS <ul style="list-style-type: none"> • Impact-protected with an approved system 	–	✓	✓
ATTACHED STRUCTURES - PORCHES/CARPORTS <ul style="list-style-type: none"> • Roof connected to beam to resist uplift • Beam connected to column to resist uplift • Column anchored to structure to resist uplift 	–	✓	✓
GABLES OVER 4' TALL - EXTERIOR (IF APPLICABLE) <ul style="list-style-type: none"> • Must have structural sheathing • Gable overhangs properly constructed 	–	✓	✓
GABLES OVER 4' TALL- BRACING (IF APPLICABLE) <ul style="list-style-type: none"> • Braced to withstand high wind pressures 	–	✓	✓
CHIMNEYS (IF APPLICABLE) <ul style="list-style-type: none"> • Properly attached to structure 	–	–	✓
OPENINGS <ul style="list-style-type: none"> • Have adequate design pressure ratings 	–	–	✓
CONTINUOUS LOAD PATH <ul style="list-style-type: none"> • Roof-to-wall connection • Wall-to-floor connection • Floor-to-foundation connection 	–	–	✓

FHDS-CAL-1704

Questions? Call 855-463-6756